



HS701 WITH FLAT SKIP

PETROL ENGINE

Brand HONDA
 Type GX270
 Pistons and displacement single-cylinder 270cc
 Max gross power 8,4 HP - 6,3 kW @3600 rpm
 Starting manual
 Fuel tank 5,3 liters
 Granted noise level Lwa 99 dB

DIESEL ENGINE

Brand KUBOTA
 Type OC 95
 Pistons and displacement single-cylinder 416cc
 Max gross power 9,4 HP - 7 kW @3600 rpm
 Starting electric
 Fuel tank 5,5 liters
 Granted noise level Lwa 101 dB

DISTRIBUTOR

Type mechanical

HYDRAULIC PUMPS

Number and type n° 3 gear pumps

TRACKS

Track tensioner grease
 Track width 180 mm
 Rollers per side 3
 Undercarriage width open/close 758-1058 mm

PERFORMANCE

Translation speed 2,2 - 3,3 km/h
 Max. inclination 15°

CAPACITY 500 kg

DUMPER BED CAPACITY

Rated volume (ISO 6483) 0,30 m³
 Struck volume 0,24 m³

OPERATING WEIGHT (without operator)

Fixed/widening undercarriage-petrol engine 565 / 650 kg
 Fixed/widening undercarriage-diesel engine. 615 / 700 kg

